

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11) Publication number:

0 632 382 A1

(12)

EUROPEAN PATENT APPLICATION(21) Application number: **94109380.9**(51) Int. Cl.⁶: **G06F 11/22**(22) Date of filing: **17.06.94**(30) Priority: **29.06.93 US 85272**(43) Date of publication of application:
04.01.95 Bulletin 95/01(84) Designated Contracting States:
DE FR GB IT(71) Applicant: **Bull HN Information Systems Inc.**
Corporation Trust Center
1209 Orange Street
Wilmington
Delaware (US)(72) Inventor: **Gilbert, Jeremy H.**
158 Concord Rd., Apt. G-5
Billerica, Mass. 01821 (US)
Inventor: **Hout, David B.**
92 Clark Street
Newton Massachusetts 02159 (US)
Inventor: **Keohane, Michael P.**
65 Oakland St.**Brighton, Mass. 02135 (US)**Inventor: **Perlow, David K.****15 Mt. Lawny Lane****Merrimack,****New Hampshire 03054 (US)**Inventor: **Peters, Daniel G.****18 Kern Dr.****Nashua,****New Hampshire 03060-4252 (US)**Inventor: **Storch, Eric J.****M4 Snow Circle****Nashua,****New Hampshire 03062 (US)**(74) Representative: **Altenburg, Udo, Dipl.-Phys. et**
al**Patent- und Rechtsanwälte****Bardehle . Pagenberg . Dost . Altenburg .****Frohwitter . Gelssler & Partner****Gallieplatz 1****D-81679 München (DE)**(54) **Method and apparatus for remote service of a host system.**

(57) A remote service facility (RSF) unit is integrated into the operating system of the host system being supported. The RSF unit utilizes a standard generic menu interface system (GMIS) unit through which a user can enter different types of commands which results in the display of a number of menu sequences for configuring how the different independently controllable components of the RSF unit will operate in performing remote support functions. The components include a problem detection and reaction component, a system action component and a callback component, each of which operatively couple to the GMIS unit. The components are integrated in a predetermined manner so that collectively, they carry out remote support according to the way in which they were configured.

EP 0 632 382 A1